Chief Executive Officer

## DEPARTMENT OF PLANNING & SUSTAINABILITY

Director

Michael Thurmond

Andrew A. Baker, AICP

## REQUIREMENTS FOR AS-BUILT LOT SURVEYS NEEDED TO OBTAIN A CERTIFICATE OF OCCUPANCY

- 1. Drawing to scale with Point of Beginning, sealed by an Architect, Engineer, or a Surveyor, licensed in the State of Georgia.
- 2. The magnetic north direction and scale used for the survey drawing.
- 3. The shape, dimensions and bearings of the property lines.
- 4. The nearest adjacent street and the driveway to the street.
- 5. The name of the nearest street with the centerline and right-of-way width.
- 6. The zoning district building set-back line and dimensions from the right-of-way or the property line
- 7. Any easements or variances on the property.
- 8. Any streams, waterways, or detention systems on the property, or distance to such (if within 200 feet) on adjacent property.
- 9. Any 100 year flood elevation on the property or adjacent property.
- 10. The slope of the driveway and landings.
- 11. Direction of surface water flow across the property.
- 12. Any retaining walls on the property and the height of the wall or the elevation to both the top and bottom of the wall.
- 13. Note any restraint system at the top of retaining walls over 30" in height.
- 14. Any encroachments on the property or the adjacent property side of the street.
- 15. Any storm drain inlets in front of the property along the property side of the street.
- 16. The dimensions from the end of the driveway radius at the curb to the nearest storm drain within 6ft of the end of the driveway.
- 17. The property address.
- 18. The height of the building and the size of the primary residence in square feet.
- 19. Identify the property zoning district with the map district, land lot, block and parcel, the percent of the lot covered by impervious surfaces, and the lot area.
- 20. The primary building and accessory structures location and shape of the property.

The tolerance for residential as-built lot surveys property lines are  $\pm$  00°30'00" bearing and 1.0 foot distance. Asbuilt lot surveys will be compared to the approved building permit drawings or final plats.